AUTO SCREENWASH™

A Low Temperature Resistant Windscreen Washer Additive
Technical Information

Auto Screenwash is a concentrated blend of solvents, detergents and surface active agents that are designed as an all-weather washer additive.
Auto Screenwash will remove a wide range of soils including grease, traffic film, oils, insect debris and general dirt.
It is designed to work in the coldest temperature and will not freeze in the windscreen washer bottle or pipes when used according to the recommended dilution rates.
It will not lead to deterioration of wiper blades and will leave a streak free, non-glaring, safe viewing area.

Primary features attributable to Auto Screenwash are:

- Resists freezing and ice formation at low temperatures;
- Effective windscreen cleaner for a wide variety of soils;
- Compatible with all current automobile materials.

Applications

This product effectively and economically removes traffic film and general grime from windscreens.
It is specifically designed to be used in on-board vehicle wash jet systems

Compatibility

Auto Screenwash is compatible with paints, plastics, metals and rubbers normally encountered in vehicular construction when used at the recommended dilution concentration.
However, care should be taken to avoid undiluted Auto Screenwash from drying onto paintwork.
Any spills etc, of the concentrated product should be rinsed off with water as soon as possible.

Certificate No. GB06/69741

Safer Solutions For Industry

© Amity Ltd 2003-15, All Rights Reserved

Health and Safety

Auto Screenwash is classified as flammable.
It possesses a low order of toxicity and the detergents are biodegradable.
Users should avoid contact of the product with eyes and skin.

See Safety Data Sheet for details.

Typical Properties

Appearance	Clear deep blue liquid
Odour	Characteristic alcohol smell
Density, g/cm^3 at 20 °C	0.952
Solubility in water	Completely miscible
pH	6.5 to 8.0 (Neat liquid)
Flash Point (Closed cup) °C	27

Auto Screenwash has a shelf life of not less than 24 months when stored in original containers between 5ºC and 35ºC.

Directions for Use

Summer use: Dilute 1 part Auto Screenwash to 40 parts water.

Winter Use: Dilute 1 part Auto Screenwash to 10 parts water.
Note: For severe cold conditions (-5 °C and below, allowing for wind chill effects), increase dilution strength to 1 part Auto Screenwash to 1 part water.

De-icing Application:
Pour or spray neat Auto Screenwash onto the affected area.
Allow the product to penetrate and liquefy the ice, then brush away using a cloth or squeegee.
Finally wipe down any paintwork with a damp cloth.

CAUTION: DO NOT leave neat Auto Screenwash in contact with paintwork for extended periods.

CONTACT DETAILS:

For UK and Rest of the World:

Amity International,
Libra House, West Street
Worsbrough Dale,
BARNSLEY
S YORKS, S70 5PG,
ENGLAND

Tel: +44 (0) 1226 770787
Fax: +44 (0) 1226 770757

For North America:

Amity International,
PO Box 5254,
1704 Denver Road,
ANDERSON,
SOUTH CAROLINA,
SC29623, USA.

Tel: 864 622 2233
Fax: 864 622 2234

E-mail: sales@amityinternational.com
Web site: www.amityinternational.com

For any further information, please contact your distributor or Amity.

In the event of any technical queries, please contact:
Mr. Ram Singh at the UK/ROW address, above, or by e-mail to:

rsingh@amityinternational.com

Packaging Details:

Auto Screenwash is available in:

- 5 L containers.