LINE MARKER SPRAY

Line Marking Paint in Handy Aerosol
Various Colours
Technical Information

Line Marker Spray is a blend of aliphatic hydrocarbon solvents, resin binders and pigment contained in an aerosol applicator propelled with a hydrocarbon based propellant system.

Line Marker is highly suitable for marking out/designating of various floor layouts and use in building applications.

Two colours are available:

- Yellow
- White

Primary features attributable to Line Marker Spray are:

- Effective marker coating;
- Tough and hard wearing, resists traffic damage;
- Easy application;
- Fast drying:
- Suitable for use on a wide variety of substrates;
- Cost effective utilisation.

Applications

Suitable for layout marking of car parks, tennis courts, warehouses, playgrounds, sports fields, structural alterations and details, etc.

Certificate No. GB06/69741

Safer Solutions For Industry

© Amity Ltd 2008-12, All Rights Reserved

Issue: 10 Aug 2012

Line Marker can be used on concrete, tar macadam, wood and composite.

Health and Safety

Line Marker Spray is classified as EXREMELY FLAMMABLE.
It is harmful by inhalation of solvent fumes during spray application and by skin contact, which will cause irritation. Users should apply the coating in well ventilated areas or by using forced air extraction.
Aerosol containers should not be stored in direct sunlight or close to heat sources.
See Material Safety Data Sheet for details.

Typical Properties

Appearance	Coloured resin film in solvent carrier
Colour	Various, As specified by user
Odour	characteristic solvent odour
Density, g/cm^3 @ 25 °C	Not available
Solubility in water	Insoluble
Flash Point (Abel closed cup, °C)	< -40 (propellant)

Coverage: a 700 ml container will give approximately 70 to 90 metres of a 50 mm wide line.

The storage life of Line Marker aerosols in original, unopened containers, at between 5 °C and 35 °C (41° to 95 °F), is not less than 24 months.

Directions for Use

Application:

NOTE: Use in conjunction with correct Line Marker Applicator unit.

1. All surfaces must be prepared, i.e. free from moisture, loose dirt/dust, oil and grease, prior to application of the marker coating.
2. Shake can vigorously for between 1 and 2 minutes after the agitator balls are heard to be free, before use.
3. Fit actuator button to upright canister.
4. Invert Can and fit into applicator.
5. Apply line coating as required, keeping applicator nozzle parallel with surface as far as is practicable.

NOTE: The speed of movement controls the density of the line.
The line edges are best defined by use of masks or masking tape.
Use a hold-off distance of between 6 and 8 inches for best effect.
Shake the container occasionally throughout applications to maintain an even distribution of contents and after use invert the can and spray briefly to clear the valve prior to storage.
Coverage may be best achieved by spraying a number of light coats to just cover the surface avoiding runs, sags and local heavy accumulations.

For heavy duty use, apply several coats as above, allowing each coat to become tack free between applications.

CONTACT DETAILS:

For UK and Rest of the World:

Amity International,
Libra House, West Street
Worsbrough Dale,
BARNSLEY
S YORKS, S70 5PG,
ENGLAND

Tel: +44 (0) 1226 770787
Fax: +44 (0) 1226 770757

For North America:

Amity International,
PO Box 5254,
1704 Denver Road,
ANDERSON,
SOUTH CAROLINA,
SC29623, USA.

Tel: 864 622 2233
Fax: 864 622 2234

E-mail: sales@amityinternational.com
Web site: http://www.amityinternational.com

For any further information, please contact your distributor or Amity.

In the event of any technical queries, please contact:
Mr. Ram Singh at the UK/ROW address, above, or by e-mail to:

rsingh@amityinternational.com

Packaging Details:

Line Marker Spray is available in:

- 700ml Aerosol containers.

Note: User to specify required colour on the order.