NEUTRACLEAN™

A Low Foam Spray Cleaner
Technical Information

Neutraclean is a low foaming, neutral, high activity spray cleaner for use in the food and beverage industries for removal of fats and grease in both hard and soft water areas.
The cleaner is based on a neutral blend of chelating, sequestering and buffering agents to make it completely safe to use on all common metals and plastics, including sensitive materials.
Suitable for use in manual cleaning and in tunnel type spray washing machines.

Primary features attributable to Neutraclean are:

- Effective, high activity, light duty cleaner;
- Low foaming;
- Easy to use,
- Cost effective utilisation.

Applications

Neutraclean is formulated to emulsify oils, fats, greases and protein.
The product finds particular application in light duty cleaning of crates and barrels/ kegs, and in tunnel washers for trays, racks and crates.
May also be successfully used for CIP (clean-in-place) cleaning

Compatibility

Neutraclean is compatible with metals, paints, plastics and rubbers normally encountered in the food and drink processing industries.

Certificate No. GB06/69741

Safer
Solutions
For Industry

© Amity Ltd 2009-16, All Rights Reserved

Issue: 7 Jan 2016

Health and Safety

Neutraclean is classified as Non-hazardous.
Users should however avoid contact with eyes.
Do not eat, drink or smoke during use.

See Safety Data Sheet for details.

Typical Properties

Appearance	Clear colourless to pale straw liquid
Odour	Very slight detergent aroma
Density, g/cm^3 @ 20 °C	1.06
Solubility in water	Completely miscible
pH (Neat) (1% Solution)	9.6 units 9.0 units

Storage life of product is 24 months in original containers when stored at temperatures between 5°C and 35 °C.

Directions for Use

Application:

Neutraclean performs best when applied using specialised spray equipment or through a high-pressure water washer.
May also be used in spray wash equipment and in manual cleaning.

Set concentration to achieve between 0.5 and 2% of Neutraclean.

Use temperature necessary to effect cleaning, ideally between 60ºC and 80ºC.

Apply the cleaner working from the base upwards, ensuring that any gaps, crevices and corners receive particular attention.
Leave cleaner in contact with surface for about 15 minutes to enable it to work. Any stubborn contaminants should be agitated using a nylon fibre pad or stiff bristle brush to assist emulsification and obtain the best results.
DO NOT ALLOW THE CLEANER TO DRY OUT.

Finally, rinse the surfaces well with water, working from the bottom upwards.

Any gross soiling can be removed by applying neat fluid using a brush followed by rinsing with water through a hosepipe.

CONTACT DETAILS:

For UK and Rest of the World:

Amity International,
Libra House, West Street
Worsbrough Dale,
BARNSLEY
S YORKS, S70 5PG,
ENGLAND

Tel: +44 (0) 1226 770787
Fax: +44 (0) 1226 770757

For North America:

Amity International,
PO Box 5254,
1704 Denver Road,
ANDERSON,
SOUTH CAROLINA,
SC29623, USA.

Tel: 864 622 2233
Fax: 864 622 2234

E-mail: sales@amityinternational.com
Web site: www.amityinternational.com

For any further information, please contact your distributor or Amity.

In the event of any technical queries, please contact:
Mr. Ram Singh at the UK/ROW address, above, or by e-mail to:

rsingh@amityinternational.com

Packaging Details:

Neutraclean is available in:

- 25 Litre containers (MOQ 8 x 25L)
- 200 Litre drum