



# TRUCKWASH™

## Vehicle Traffic Film Remover & Polish

### Technical Information

Truckwash is a blend of alkali cleaners, detergents and surface-active agents this is designed to remove the heaviest traffic film contamination from transport vehicles and associated equipment. The product also contains special waxes to enhance the shine and protection of cleaned surfaces.

Primary features attributable are:

- Concentrated formulation for ease of use and economy;
- Effective heavy duty traffic film remover;
- Incorporates water repelling shine and protection additives;
- Detergents are biodegradable.

---

### Applications

This powerful cleaner is ideal for the removal of oil, grease and general traffic film from:

- Trucks;
- Buses;
- Trailers, etc.
- Canvass covers and side curtains.

Truckwash has also found use for cleaning and degreasing of chassis, engine blocks, fifth wheels, plant and equipment, etc.

Truckwash is designed for use within brush and pressure washing systems. Truckwash can also be used by hand washing.

---

### Compatibility

Truckwash may be safely applied to steel, aluminium, titanium, magnesium, zinc and other metal surfaces and is safe to use on vehicular paints and Trailer materials.



Certificate No. GB06/69741

Safer  
Solutions  
For Industry

## **Health and Safety**

Truckwash is classified as Irritant.

Users should avoid eye and skin contact and any spills can create a slip hazard if not washed away with water.

Detergents are biodegradable.

The product is not classified as Flammable.

See Safety Data Sheet for details.

## **Typical Properties**

Appearance	Pale Yellow coloured liquid
Odour	Detergent odour
Density, g/cm <sup>3</sup> at 20 °C	1.09
Solubility in water	Complete
pH	13.5 (Neat gel) 12.1 (1% solution)

Storage life of Truckwash in original, unopened containers, at between 0 °C and 35 °C (32° to 95 °F), is not less than 2 years.

## **Directions for Use**

### **Dilution Rate:**

Dilution is determined by the degree of soiling to be cleaned, as follows:

- Light soil: 1 part Product to 50 parts water.
- Medium soil: 1 part Product to 20 parts water.
- Heavy soil: 1 part Product to 10 part water.

### **Application:**

Pre-dilute the cleaner according to the nature and degree of the soil and place in the detergent tank of the spray applicator equipment.

Adjust the detergent feed rate to achieve the cleaning action required.

Allow the detergent cleaner to work for a few minutes before rinsing off.

Remove by washing with water.

Note: For best results, do not allow cleaning material to dry out on any surface prior to rinse off.

## **CONTACT DETAILS:**

### For UK and Rest of the World:

Amity International,  
Libra House, West Street  
Worsbrough Dale,  
BARNSELY  
S YORKS, S70 5PG,  
ENGLAND

Tel: +44 (0) 1226 770787  
Fax: +44 (0) 1226 770757

**E-mail:** [sales@amityinternational.com](mailto:sales@amityinternational.com)

**Web site:** [www.amityinternational.com](http://www.amityinternational.com)

For any further information, please contact your distributor or Amity.

In the event of any technical queries, please contact:  
Mr. Ram Singh at the UK/ROW address, above, or by e-mail to:

[rsingh@amityinternational.com](mailto:rsingh@amityinternational.com)

---

## **Packaging Details:**

Truckwash is available in:

- 30 Litre containers.
- 210 Litre containers.